

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) Publication number:

0 277 396
A1

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: **87202659.6**(51) Int. Cl.⁴: **A01J 7/00 , A01K 13/00**(22) Date of filing: **30.12.87**

A request for addition of a missing page of the originally filed application documents has been filed pursuant to Rule 88 EPC. A decision on the request will be taken during the proceedings before the Examining Division (Guidelines for Examination in the EPO, A-V, 2.2).

(30) Priority: **02.02.87 NL 8700249**(43) Date of publication of application:
10.08.88 Bulletin 88/32(84) Designated Contracting States:
AT BE CH DE ES FR GB IT LI LU NL SE

(71) Applicant: **Multinorm B.V.**
Hoofdweg 1278
NL-2153 LR Nieuw-Vennep(NL)

(72) Inventor: **Verbrugge, Jeroen Klaasjan**
Hugo van Rijkenlaan 8
NL-2612 JR Delft(NL)
Inventor: **Borgman, Fokke Pieter**
J.B. Kanweg 290
9439 TH Witteveen(NL)

(74) Representative: **Holijtink, Reinoud et al**
OCTROOIBUREAU ARNOLD & SIEDSMA
Sweelinckplein 1
NL-2517 GK Den Haag(NL)

(54) **Method for cleaning a teat of a female animal, milking method and cup for use with above mentioned methods.**

(57) This method of cleaning a teat (3) of a female animal makes use of a cup (1) provided with an opening (7) for flushing washing and/or rinsing agent along said teat (3). Preferably this method is included in automatic milking equipment.




FIG. 2

EP 0 277 396 A1

Method for cleaning a teat of a female animal, milking method and cup for use with above mentioned methods

The present invention relates to a method for cleaning and/or rinsing a teat of a female animal.

The teats of a female animal have been cleaned up to the present time before and after milking of that female animal by a farmer by hand, for example with a wet cloth or a water jet, which may or may not be provided with a disinfecting agent or soap.

This known cleaning method has the disadvantage that the cleaning will either not be carried out often or not be done well.

The purpose of the invention is to provide a cleaning method for a teat of a female animal which ensures a meticulous wet cleaning of a teat of this female animal.

This object is achieved with the cleaning method as claimed in claim 1.

In preference the cleaning method as claimed in claim 2 is applied so that just as in the milking of a cow or goat a movement will be performed by a flexible wall on a teat of this cow or goat, which will result in the washing agent combined with a simultaneous massaging movement making an optimal contact with the teat. Any dirt that may be adhering to the teat will come loose as a result.

In addition this invention provides a method for milking a female animal, whereby the cleaning method can be performed in a cup used for milking.

The invention further provides a cup for use with the cleaning method, as well as a milking set for four cups.

Further features, details and advantages of the current invention will become apparent with reference to a drawing, in which:

fig. 1 shows partly in section a first embodiment of a cup for implementing a method according to the invention for cleaning a teat of a female animal;

fig. 2 shows schematically a second embodiment of a cup for implementing a method according to this invention;

fig. 3 shows a third embodiment of a cup for implementing a method according to this invention; and

fig. 4 shows perspectively a milking set provided with four cups in accordance with the invention.

A cup 1 (fig. 1) is placed on a handle 2 by a farmer under a teat 3 of a cow, of which cup 1 of a flexible wall 4 of an inner casing 5 is accommodated for instance in an outer casing 3, e.g. of metal. Supplied (arrow S) via a connection 7 to the upper part of teat 3 is a washing agent, for exam-

ple water, which may or may not be provided with disinfectant agent or soap. In order to improve the washing action a pulsating pressure variation is preferably applied via arrow V over the wall of the inner casing 4, whereby the teat is massaged and the washing agent will make good contact with teat 3. The passage to an outlet 8 of the cup could if desired be pressed virtually shut beneath teat 3 so that a turbulent driving action is caused, which will improve cleaning still further. The washing agent will leave cup 1 via outlet 8. Underpressure is preferably connected to outlet 8 so that the washing agent will be drawn off easily and the teat 3 can be placed easily in cup 1. The upper piece 9 of inner casing 5 has a sealing action against the udder 10 of the cow.

Cleaning using cup 1 can take place both before and after milking. Prior to milking the washing will usually be done with water - rinsing -; only after milking will soap or disinfecting agent usually be added to the washing agent, so that they will not get into the milk.

In another embodiment of the method according to the invention (fig. 2) a cup 23 for cleaning is likewise suitable for milking. Cup 23 is provided with an outer casing 24, e.g. of metal, and an inner casing 25 of flexible material, between which a milking movement for a teat 27 of a cow can be generated via a conduit 26 by a milking machine (not shown). Cup 23 is provided with a cushion 28 for sealing against the udder and with conduits 29 for supply of a washing agent, for instance water, extending into the openings 61 as well as through outer casing 23 and inner casing 25. Line(s) 29 are preferably situated equidistantly around the periphery of cup 23 and ensure a good washing around the teat 27. It is of course possible to arrange only one line 29. Lines 29 are connected onto a ring line 30 around the outer casing, from which ring line another line 31 leads to a pump 32. The washing agent moves via a discharge 33, which is also suitable for the discharge of milk and which is held under underpressure, to a four-way valve 34 which in the situation drawn leads to line 35 for discharge of washing agent. Valve 34 can also be switched via control member 36 to a line 60 for discharge of milk. The four-way valve 34 can likewise place the cup in contact with the ambient pressure via bleed opening 19, which will result in cup 23 dropping off the teat. To improve liquid transport in the discharge lines a small orifice (diameter 0.1-0.5 mm) is arranged in line 33 for leakage of ambient air.

After switching off of pump 32 and at a moment in time t_2 that is later than this switching off,

control member 36 will switch the four-way valve 34 over to the position in which milk can be carried to the line 60 and the milk discharge can take place. Shown schematically is the link between pump 32 and control member 36 via lines 37, timing element 38 and line 39.

In another method according to the invention (fig. 3) a milk quality meter 40 is applied which is arranged on the conduit 33 and which measures the conductivity of milk or washing agent for discharge, as a result of which a regulating member 41 can determine into which position control member 42 must actuate the four-way valve 34. Teat 27 will thus be washed, whereby washing is performed optimally by way of a pulsating via conduit 26 and milking is simultaneously started up; it will take 5-15 secs. before milk will flow fully out of teat 27 after generating of a pulsating movement, this period of time usually being sufficient for complete cleaning of teat 27. The pulsating movement or pulse frequency during cleaning and milking are different so as to lose as little milk as possible during the washing phase. The regulating member 41 determines on the basis of the milk quality measured by the milk quality meter 40 at which precise moment the control member 36 must switch over the four-way valve 34. With the method as in fig. 3 cleaning of the teat is carried out from beneath the teat using pump 32 via a ring line 18 and upward directed spray nozzles 17. It is herewith possible to use as cup 16 an upright milking cup provided on the underside with spray nozzles 17. With the method as in fig. 1 and 2 the upper portion of the teat is better washed than with the method as in fig. 3. There is furthermore less chance of dirt getting into the teat opening, the so-called teat-orifice.

In order to prevent any disinfectant agent or soap becoming mixed in with the milk it is recommended that a first washing of teat 27 prior to milking is carried out using only water as washing agent, while a washing performed subsequent to milking is carried out using soap or disinfecting agent in the washing agent.

If a teat of a cow is infected - mastitis - a milk quality meter (not shown) can be incorporated which in addition to measuring the difference between milk and washing agent also measuring the difference between milk and washing agent also measures the difference between milk suitable for consumption and milk not suitable for that purpose (mastitis milk).

The milking set 43 (fig. 4) is further provided with a central feed line 45 and a central connection 72 for supply of pulsating underpressure. The central member 44 is provided with a line 70 for discharge of milk suitable for consumption and a line 71 for discharge of milk not suitable for con-

sumption and for washing agent discharge.

It is noted finally that the above described cleaning method as well as the milking method using this cleaning method are preferably employed in a automatically operating milking system, as described in the European patent application 86.201338.0, the European application 86.202380.1 and the Dutch patent application 86.02942 from the same applicant, the content of which must be considered as interpolated herein.

Claims

1. Method for cleaning a teat (3, 27) of a female animal, whereby after fitting of a cup (2, 1, 16) around said teat (3, 27) a washing and/or rinsing agent is flushed along said teat (3, 27) of the female animal via at least one opening in said cup.

2. Cleaning method as claimed in claim 1, wherein during washing a pulsating pressure variation is generated over a flexible wall (4) arranged in the cup for accommodation of the teat.

3. Cleaning method as claimed in claim 1 or 2, wherein via an outlet of the cup (1, 16, 23) a vacuum is generated in said cup.

4. Cleaning method as claimed in claim 1, 2 or 3, wherein the washing agent in the proximity of the upper part of the teat is washed downward.

5. Cleaning method as claimed in any of the claims 1-4, wherein the washing agent comprises water, disinfecting agent and/or soap.

6. Method for milking a female animal, whereby at least one cup is arranged around at least one teat of a female animal and whereby in said cup a milking movement is performed on said teat, wherein prior to discharge of the milk out of said cup the cleaning method as claimed in any of the claims 1-5 is applied.

7. Milking method as claimed in claim 6, wherein after termination of the supply of washing agent the outlet of the cup is coupled at a predetermined moment in time to the milk discharge line.

8. Milking method as claimed in claim 6 or 7, located on the milk outlet of the cup is a milk quality meter determining the quality of the milk and that a four-way valve linking said milk outlet to a milk discharge line and a discharge line for washing agent is controlled by the influence of signals given by said milk quality meter.

9. Cup, comprising an outer casing and an inner casing located therein of flexible material in which the teat of the female animal can be accommodated, wherein at least one opening for supply of washing agent is arranged in said inner casing.

10. Device for performing the method as claimed in any of the claims 1-8.

11. Milking set provided with at least two cups as claimed in claim 9.

5

10

15

20

25

30

35

40

45

50

55

4




FIG. 1




FIG. 4




FIG. 2




FIG. 3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 87 20 2659

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
X	GB-A- 918 766 (E.D. DYKE) * Page 3, lines 33-81; figure 3 * ---	1,3-7,9 -11	A 01 J 7/00 A 01 K 13/00
A	DE-A-2 622 794 (ALFA-LAVAL AGRAR GmbH) * Page 13, lines 8-22; figure 1 * ---	1,6,9- 11	
A	EP-A-0 207 572 (VAN DER LELY) ---		
A	US-A-4 149 489 (R.E. UMBAUGH et al.) -----		
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int. Cl. 4)
			A 01 J A 01 K
Place of search THE HAGUE		Date of completion of the search 29-02-1988	Examiner NEHRDICH H.J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			